

NON-PROVISIONAL PATENT APPLICATION

TITLED:

**AUTOMATED METER READING SYSTEM,
COMMUNICATION AND CONTROL NETWORK FOR
AUTOMATED METER READING, METER DATA
COLLECTOR, AND ASSOCIATED METHODS**

Inventor:

**Jon A. Boaz
7008 Shepherds Glen
Colleyville, Texas 76034**


CERTIFICATE OF MAILING 37 C.F.R. 1.10

"Express Mail" Mailing Label Number: EV 342456593 US

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office To Addressee" service with sufficient postage on the date indicated below and is address to: Box Conversion App; Commissioner for Patents, PO Box 1450, Alexandria, VA 22313-1450.

February 13, 2004

Date


Dorina Waiters

AUTOMATED METER READING SYSTEM, COMMUNICATION AND CONTROL NETWORK FOR AUTOMATED METER READING, METER DATA COLLECTOR, AND ASSOCIATED METHODS

RELATED APPLICATIONS

[0001] This is a non-provisional patent application, which claims the priority of provisional patent application U.S. Serial No. 60/447,815, filed February 14, 2003, titled Automated Meter Reading System, Communication and Control Network for Automated Meter Reading, Meter Data Collector, and Associated Methods, and which is incorporated herein by reference in its entirety.

BACKGROUND

1. Field of the Invention

[0002] The present invention relates in general to the field of utility meters. More particularly, the present invention relates to automatic equipment, systems, networks, and software for remote reading of utility meters, such as electric, gas, water, or steam meters.

2. Description of Related Art

[0003] Utility companies and municipalities for many years have been burdened with the labor intensive and cumbersome task of manually collecting meter readings, managing data from the field into the accounting area, and managing the billing and collection of invoices. Typically each customer is provided with a mechanical utility meter for each individual service provided, for example, a meter for water, a meter for steam, a meter for gas, and a meter for electric power. A periodic reading of the utility meter is necessary to determine the usage and to bill the customer for the amount used. These meters are normally manually read using utility company or municipality employees physically visiting each meter at the customer's location, reading the meter, and recording the previous month's usage into a written route book for delivery to accounting personnel. This process is costly, is time consuming, and can involve various risks to personnel involved in manually collecting meter data. The process involves labor, motorized transportation, and numerous employee overhead-related costs. Once the readings from the

meter are obtained, accounting personnel manually transfer the readings into a database for billing and collection of the invoices for service.

[0004] Manually reading the meters often results in numerous other expenses including those related to human error. For example, a high bill caused by an incorrect manual read or estimated read often motivates customers to pay later, resulting in increased working capital requirements and corresponding expenses for the utility. Additionally, the utility has to handle the customer complaints (a call center cost) and may have to read the meter again to verify the error. As the complaint progresses, the utility faces administrative costs associated with routing and processing the complaint from the call center to the meter department. An additional cost includes the potential loss of a customer who, even after resolution, feels the process was such an excessive burden as to prompt the customer to switch utility providers.

[0005] Recently, hand-held reading units have been developed that typically provide a data collection unit attached to the consumer's utility meter having some form of data transmitter. The unit or system has some form of receiver. There are different variations in methodology of receiving the data. One methodology of hand-held "local" collecting meter reading requires an operator having a meter or collection unit interrogation device to be in close physical proximity of the meter to obtain the meter reading and transport the data to a central computer such as shown in U.S. Patent No. 5,559,894 by Lubliner et al. titled "Automated Meter Inspection and Reading" and U.S. Patent No. 5,856,791 by Gray et al. titled "Port Expander For Utility Meter Reading." For example, in a radio drive-by or walk-by unit, a utility service vehicle having a mobile receiver mounted in a service vehicle or a utility work having a hand-held unit passes by the consumer's facility to receive the data from the meter. As the vehicle or hand-held unit passes near the electric meter, the receiver emits a signal to the collection unit, which causes the collection unit to transmit or send its meter reading data to the receiver. This consumption data is then stored and later entered into a billing system. This approach, however, still requires the manual visit to each meter location and time downloading the data to the billing system. Nevertheless, the physical meters can be read much more quickly which reduces manpower, vehicular, and soft costs. Also, the data is transferred from the mobile receiver to the database, which again reduces manpower and data handling. This methodology also has a benefit to the customer of preventing intrusion into the customer's premises and improved accuracy of the reading. Remaining system negatives, however, included prohibitive capital costs, i.e., vehicles,

and software and hardware requirements, and providing a reliable and cost-effective power solution for the individual radio transmitter in the individual meters.

[0006] Recently, automatic meter reading ("AMR") has been developed. Automated meter reading has become more desirable than using meters that require manual reading and recording of the consumption levels. AMR consists of technologies and methods to remotely read a plurality of electric meters, such as a consumer base for an electric power supply company, into a billing database by installing or utilizing fixed networks that allow billing or meter usage data to be transmitted without human intervention to a host computer having the billing database. AMR produces many benefits and several companies such as Hunt Technologies, Schlumberger, CellNet, Itron, Amco Automated Systems, and Distribution Control Systems have developed AMR units. For the utility, reading meters without setting foot on customer's property substantially reduces risks associated with climbing over fences, slipping on ice and snow, dangerous animals, snakes, and spiders, and other types of risks which in turn, result in significant savings in liability insurance, disability benefits, and worker turnover/replacement. For the customer, reading meters without entering customer's property provides a less intrusive service and reduces criminal activity such as when a criminal manages to gain entry into a customers property by posing as a meter reader. Moreover, the need for a higher frequency of meter reading is increasing, e.g., daily, hourly, or every 15 minutes in order to take advantage of real time pricing. Also, the amount of data is increasing, due to the necessity to bill on more than just consumption, e.g., time of use. Thus, automated recording and reporting of the utility usage at customer sites is rapidly replacing the manually read utility meters.

[0007] AMR system uses a dial-up modem in the collection unit to dial a remote billing system and transmit its reading data via telephone lines such as shown in U.S. Patent No. 6,163,602 by Hammond et al. titled "System and Method for Unified Telephone and Utility Consumption Metering, Reading, and Processing" and U.S. Patent No. 5,128,988 by Cowell et al. titled "Telephone Switched Network, Automatic Meter-Reading System Based Upon Service Address." In the past, there has been on-site meter reading equipment having modem capability capable of receiving telephone calls from a central office through the use of special equipment located at the telephone company, and there have also been on-site meters with modems which were capable of placing telephone calls to the central office. In general, these systems incorporate an auto-dial, auto-answer modem in each customer site to receive interrogation

signals from the telephone line and to formulate and transmit meter readings via the telephone line to the utility company. These systems record information on utility usage and periodically dial into a central office to report the utility usage for recording and billing purposes. This methodology provides two-way communication and control between the meter and the central office. The modem shares the telephone line with the customer's normal usage, such as incoming and outgoing voice communications. Such sharing requires that the system be able to recognize when the telephone line is in use, and to delay demanding use of the telephone line until it is free. Steps must be taken to prevent the data communications system from interfering with other uses and to prevent other uses from corrupting the transmitted data.

[0008] A variation of this methodology includes using the power line as a carrier medium. This approach connects the meter through the power lines and relays the meter reading over the power lines to the utility company. This approach, however, can require a complicated infrastructure to be installed. Power lines operate as very large antennas and can receive a large amount of noise. Therefore, signal-cleaning filters must be installed periodically along the power lines to attenuate the noise. These filters can be very expensive. Also, the connections often are at line voltage, making it more dangerous and time consuming to install.

[0009] Another problem with expanding the use of control systems technology to such distributed systems are the costs associated with the sensor-actuator infrastructure required to monitor and control functions within such systems. A more modern approach to implementing control system technology is to install a local network of hard-wired sensors and actuators along with a local controller. Not only is there expense associated with developing and installing appropriate sensors and actuators but the added expense of connecting functional sensors and controllers with the local controller, and the cost of the local controller. This methodology is also quite intrusive as the cables must be run to physically interconnect the various nodes in the network. An alternative variation includes interfacing the meter with a community cable television system. In addition to the high cost of installation, however, such a system is not useable in areas without access to a cable system. Moreover, networks that are interconnected with cables are subject to physical disruption of the cables.

[0010] Recently, wireless networks have been developed. These networks, typically installed in a point-to-point loop configuration, are used to collect information from and to disseminate information to individual nodes of the network. In conventional wireless networks

using a point-to-point loop configuration, each node in the network is interconnected and communicates with two neighboring nodes. Information or commands are passed from node to node around the point-to-point loop until they arrive at a master node. The master node is used to communicate information that is gathered to a central station or to accept and distribute information received from a central station throughout the network. These conventional wireless networks, however, have limitations. For example, because these conventional wireless networks generally have a point-to-point loop configuration, when one node is disabled, the integrity of the entire network can be affected. Moreover, if the master node of such a conventional network is disabled, the network can become isolated.

[0011] Other variations in methodology include using data channels in wireless telephone systems to transmit usage data to a remote billing system via a wireless telephone network, such as PCS, satellite, or cellular. Other methodologies also include the use of low earth orbiting satellites. Building, launching and maintaining a fleet of satellites, however, is very expensive.

[0012] Yet another methodology includes the use of small RF transmitters. Because systems having sufficient range normally are subject to regulations and licensing requirements that are prohibitively expensive, however, the centralized wireless control systems for locally distributed devices using RF transmitters have not been widely utilized. Also, systems that are sufficiently powerful to be used in widely distributed installations are unnecessarily expensive in smaller installations. Additionally, there is limited availability of RF carrier frequencies, and potential interference with other nearby systems that might be operational.

[0013] Further AMR servers have been developed, such as shown in U.S. Patent No. 6,088,659 by Kelley et al. titled "Automated Meter Reading System," in attempts to address the metering data management needs of entities involved in energy distribution. Such AMR servers use an open, distributed architecture that collects, loads, and manages system-wide data collected from energy meters and routes data automatically to upstream business systems. Although such AMR servers may address some meter data management concerns, these systems still fail to address communication concerns set for the above with respect to collecting billing or usage data and transmitting the data to a control center, e.g., perhaps having an AMR server.

SUMMARY OF THE INVENTION

[0014] In view of the foregoing, Applicant has recognized a need to automate and transform the process of metering electricity, gas, water, steam, and the like, while reducing costs, adding value, enhancing service, and decreasing time of collection.

[0015] When utilities such as gas, electricity, or water are most expensive to the customer, they are also correspondingly most expensive to the utility company. Accordingly, Applicant also has recognized a need for control systems technology to such distributed systems that provide the customer with information to reduce costs and help the utility by reducing demand at peak hours. Applicant further has recognized a need for a fixed network AMR that includes a multifunction data collector capable of transmitting meter readings for multiple meters to the control center and relaying meter readings of other collectors.

[0016] An embodiment of the present invention advantageously provides a distributed network system including at least one utility meter, and preferably a plurality of utility meters, at least one sensor interfaced with each meter, a meter data collector positioned in communication with the at least one sensor to receive meter usage reading data. The system also includes a remote automatic meter reading control center including a computer, e.g., a server, for gathering and processing the usage reading data. The system also includes system software associated with the computer of the remote control center and associated with the collector. Preferably, the system software has network software including a network protocol, e.g., preferably a preselected application layer protocol, to communicate over a network connected to each of the meter data collectors and meter sensors. The network software is preferably capable of querying each meter data collector and assigning the meter data collector a physical location based on the actual physical location with reference to other collectors or "nodes."

[0017] The meter data collector gathers a usage reading from each sensor communicating with the collector and transmits the data to and receives instructions from the control center. The collector advantageously can include a power module, a controller, a telemetry module, a memory module, a multiple input connection block and a housing preferably meeting NEMA standards, as understood by those skilled in the art, to enclose the unit. In an embodiment, the multiple input connection block includes expandable or input/output ports capable of accepting either digital or analog input. In embodiments of the system, each of the sensors can be tailored to the specific type of meter to be read. For example, for a water meter, the sensor or the

collector itself can be attached at the same point that the outside dial attaches. For the gas meter and steam meter, a pulse initiator can be added to the respective meter to digitize the usage. For the electric meter, a pulse board can be added.

[0018] In an embodiment of the system, the collector uses frequency hopping radio frequency (RF) electromagnetic radiation as understood by those skilled in the art. Use of an RF based network advantageously reduces data transmission cost, is flexible, and has low deployment costs. In some embodiments, the system uses low-power RF transmissions. In a medium-range embodiment, the range between collectors and the control center for associated substations can be between 500-1500 meters. In a long-range embodiment, that distance can be between 2000-6000 meters. In an embodiment, the collector is powered through a connection to the electric utility meter. Another embodiment for powering the collector includes the use of a cable having an electrical outlet interface. An alternative embodiment for powering the collector includes use of batteries.

[0019] Functionally, data is acquired from the sensor interfaced with its respective individual meter. Data is obtained by the collector, from the meter sensor, where it is temporarily stored. In an embodiment, all metering data is date and time stamped to provide an accurate record of the read. Typically and functionally this data is then forwarded directly to the control center or a substation if within range and not blocked or impeded by a physical structure or other obstacle. If the collector is not within range, the data is forwarded to another collector associated with a location closer to the control center or a substation, to an intermediate collector, to be forwarded to the control center or substation. In essence, the network structure turns every collector into an individual network node capable of transmitting its respective meter indication data from either "nodes." Thus, an embodiment of the present invention advantageously provides a self-healing network having minimal infrastructure that significantly reduces line-of-site issues whereby a physical structure may block the transmission of an individual collector. Advantageously an embodiment of the present invention also allows for scalability as the addition of a new collector at a new location is merely tantamount to adding an additional "node" to the network. In the preferred implementation, however, the network node level between the various nodes and either the control center or a substation can be limited to 15. Advantageously the system provides for both passive and dynamic execution of a meter read. Although the control center can prompt for

an additional read if greater delay accuracy is required, the collector can send a current read to the control center every 15 minutes.

[0020] The system control center further includes at least one computer, e.g., a server, including a processor to store, process, and manipulate data gathered by the collectors and transmitted to the control center. The control system correspondingly includes at least one data storage medium to provide for meter record storage and retrieval. The data storage medium is adapted to interface with software for storing and updating a database. The database includes a table(s) to assign the at least one collector physical address and assign various usage data. The usage data is compared to a temporal usage rate to formulate and store with the meter data to a record of consumption totals.

[0021] The computer system also advantageously provides various functions of the utility's control center with the meter data. Regarding a billing office, accurate timely data insures efficient monthly consumption billing on a customer-requested date. Regarding the customer service department, the collection of daily metering data enables the utility to efficiently manage final reads and switching as well as customer complaints without the expense of dispatching someone to the field to re-read the meter. Regarding the scheduling department, daily reads on all the meters in the service territory significantly improves load-forecasting accuracy. Regarding the loss management department, the collection of tamper status information on a daily basis enables quick identification and resolution of energy theft. The marketing department, daily reads allows targeting and delivery of new rates or selectable billing dates to specific customers. Daily reads on a customer that has multiple meters in multiple locations also enables delivery of aggregated billing services, or same-day billing services for all its locations. For the engineering/distribution planning department, daily data collection provides an accurate, continually updated picture of daily load that can be isolated to a specific area, enabling optimum efficiency and system planning, outage management, equipment installation, and maintenance. Additionally, frequent data collection of actual usage can be compared to estimating usage, which enables quick and efficient reconciliation and settlements between utilities, generators, ESPs, and power exchanges. For the end customer, access to daily usage information increases customer satisfaction by enabling more efficient management of energy usage and predicting energy expenditures more accurately.

[0022] Advantageously, an embodiment of the system and system software provides for the customer an increased understanding of its usage patterns. This understanding enables the proper selection of rate options, supplier choices, aggregation and bulk purchasing opportunities and efficient forecasting and settlements. The system also advantageously provides for power outage notification and restoration notification. Additionally, the system provides for billing options such as selectable billing dates, selectable billing frequencies, and on-demand billing, which are not cost-efficient when using manual reading of the meter.

[0023] Advantageously, an embodiment of the system and system software provides for the utility increased distribution effectiveness including improved facilities and infrastructure planning, maintenance improvements, improved system reliability, operational efficiencies, improved customer service, outage detection, forecasting and settlements, and load balancing and planning. The system software also advantageously provides for data warehousing and data mining, historical patterns and expectations analysis, analysis for new rates structures, and services bundling such as aggregation of billing to an individual customer, outage detection monitoring, and Internet access to the data

[0024] Advantageously, an embodiment of the system and system software additionally benefit the utility by providing cost savings on regular "on-cycle" meter readings, the ability to obtain more easily (e.g., instantly) final meter reads for opening/closing accounts, stream-lined high bill investigations, the ability to flag potential high consumption before consumers get a high bill, help in pinpointing system losses and detect theft in service. Additionally, the system and system software also advantageously enable more frequent reads with minimal incremental cost, enable custom billing dates, support customized rates for large customers, provide detailed consumption information to customers to provide watchdog services, like leakage monitoring, improved cash flow management due to a reduction in bill contests, improved revenue forecasting by tying detailed consumption information to production data and expected billings, enable more sophisticated rates, and reduce billing adjustments.

[0025] The system and system software of the present invention also advantageously provide for reduced capital costs due to the reduced number of vehicles necessary to physically service the meters, labor savings including the reduction in staff hours for meter reading and meter reading-related customer service, savings on vehicles and miscellaneous costs associated with meter reading, and provide for increased revenues from reducing system losses or replacing older

inaccurate meters. Also, an embodiment provides the utility company with the ability for "back-end" billing and accounting software to bundle with the collector, preferably the RCU-41, and associated system software to provide a gathering, transmission, billing, collection and reporting solution.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] So that the manner in which the features and advantages of the invention, as well as others which will become apparent, may be understood in more detail, a more particular description of the invention briefly summarized above may be had by reference to the embodiments thereof which are illustrated in the appended drawings, which form a part of this specification. It is to be noted, however, that the drawings illustrate only various embodiments of the invention and are therefore not to be considered limiting of the invention's scope as it may include other effective embodiments as well.

[0027] FIG. 1 is a schematic view of an automated meter reading network system according to an embodiment of the present invention;

[0028] FIG. 2 is schematic view of an automated meter reading network system according to an embodiment of the present invention;

[0029] FIG. 3 is a schematic view of an automated meter reading network system according to an embodiment of the present invention;

[0030] FIG. 4 is a schematic view of an automated meter reading network system according to an embodiment of the present invention;

[0031] FIG. 5 is a schematic view of an automated meter reading network system according to an embodiment of the present invention;

[0032] FIG. 6 is a schematic view of a plurality of meter data collectors defining a plurality of remote collection units each positioned on a separate building and in communication with a main utility center according to an embodiment of the present invention;

[0033] FIG. 7 is a schematic view of a plurality of meter data collectors defining a plurality of remote collection units each positioned on a separate building and in communication with a main utility center according to an embodiment of the present invention;

[0034] FIG. 8 is a schematic view of a plurality of meter data collectors defining a plurality of remote collection units each positioned on a separate building and in communication with a

water tower having a meter data collector or repeater mounted thereto and in communication with a main utility center according to an embodiment of the present invention;

[0035] FIG. 9 is schematic view of a meter data collector defining a remote data collection unit and having a plurality of data collection ports each for a plurality of different utility meters or other uses according to an embodiment of the present invention;

[0036] FIG. 10 is an exploded perspective view of a meter data collector defining a remote data collection unit associated with a first embodiment of a housing according to an embodiment of the present invention;

[0037] FIG. 11 is an exploded perspective view of a meter data collector defining a remote data collection unit associated with a second embodiment of a housing according to another embodiment of the present invention;

[0038] FIG. 12 is an exploded perspective view of a meter data collector defining a remote data collection unit associated with a third embodiment of a housing according to yet another embodiment of the present invention;

[0039] FIG. 13 is flow diagram of a control read state of a collector according to an embodiment of the present invention;

[0040] FIG.14 is a flow diagram of the control write state of a collector according to an embodiment of the present invention;

[0041] FIG. 15A-15C are tables of an embodiment of a frequency list for transmit and receive settings according to an embodiment of the present invention.

DETAILED DESCRIPTION

[0042] The present invention will now be described more fully hereinafter with reference to the accompanying drawings, which illustrate embodiments of the invention. This invention may, however, be embodied in many different forms and should not be construed as limited to the illustrated embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to

those skilled in the art. Like numbers refer to like elements throughout. The prime notation, if used, indicates similar elements in alternative embodiments.

[0043] As illustrated in FIGS. 1-15E, an embodiment of the present invention provides a distributed network system including a multifunction collector or controller, a utility meter, and at least one sensor, e.g., an encoder, interfaced with the meter. The sensor is positioned in electrical communication with the collector in order to provide a meter usage reading data. The system also includes a remote control center for gathering and processing the usage reading data. The system also includes system software. Preferably, the system software has network software including a network protocol (preferably an application layer protocol, described below) for communicating over a network connected to each of a plurality of controllers if desired, and at least one sensor. The network software is preferably capable of querying at least one collector and assigning the at least one collector a physical location based on the actual physical location with reference to the other collectors or "nodes" within a network.

[0044] As shown in FIGS. 3-4, the collector gathers a usage reading from the at least one sensor and transmits the data to and receives instructions from the remote control center. The multifunction collector includes a power module, a controller, a telemetry module, a memory module, a multiple input connection block and a housing preferably meeting NEMA standards to enclose the unit. In an embodiment, the multiple input connection block advantageously can include input/output expressions modules or ports capable of accepting either digital or analog input. In embodiments of the collector, the sensor can be tailored to the specific type of meter to be read. For example, as understood by those skilled in the art, regarding a water meter, the sensor or the collector itself can be attached at the same point that the outside dial attaches. For the gas meter and steam meter, a pulse initiator can be added to the respective meter to digitize the usage. For the electric meter, a pulse board can be added.

[0045] In an embodiment of a system, such as shown in FIG. 5, the system uses frequency hopping radio frequency (RF) electromagnetic radiation as understood by those skilled in the art. Use of an RF based network reduces data transmission cost, is flexible, and has low deployment costs. In an embodiment of a system, the system uses low-power RF transmissions. In a medium-range embodiment, the range between collectors and the control center for associated substations can be between 500-1500 meters. In a long-range embodiment, that distance can be between 2000-6000 meters. In an embodiment of a collector, the collector is powered through a

connection to the electric utility meter. Another embodiment for powering the collector includes the use of a cable having an electrical outlet interface. An alternative embodiment for powering the collector includes use of batteries.

[0046] As shown in FIGS. 3-4, functionally, data is acquired from the sensor interfaced with its respective individual meter. Data is obtained by the collector, from the meter sensor, where it is temporarily stored. All metering data can be date and time stamped to provide an accurate record of the read. As shown in FIG. 5, typically and functionally, this data is then forwarded directly to the remote control center or a substation if within range and not blocked or impeded by a physical structure or other obstacles.

[0047] The collector, as shown in FIG. 4 and as described herein, can have the following features:

Functional Specifications:

- power source: 5VDC or 120, 240VAC transformer
- tamper detection: meter removal, outage detection
- operating temperatures: -40° to +85°C
- operating humidity: 5 to 95% non-condensing relative humidity
- FCC Compliance: Part 15 certified
- Certification: ANSI C12 Standards

Operation Specifications:

Radio Module:

- Transmit and receive frequency: 902-928 MHz
- CRC error checking on every message

Base Board

- Discrete Inputs (4 pt.) Optically isolated 5VDC
- Five I/O expansion modules

Physical Specifications

- ABS plastic housing UL-94-0
- 10"H X 10"W X 5"D
- Pole or wall mountable

I/O Expansion Modules

- Discrete input (4 pt.) optically isolated 5VDC
- Discrete input (4 pt.) optically isolated 12VDC
- Discrete input (4 pt.) optically isolated 24VDC
- Discrete input (2 pt.) optically isolated 5VDC
- Discrete input (2 pt.) optically isolated 12VDC
- Discrete input (2 pt.) optically isolated 24VDC
- Discrete output (4 pt.) relay 12-280VAC 5A
- Discrete output (4 pt.) relay 0-60VDC 5A
- Discrete output (4 pt.) relay 0-60VDC 10A
- Discrete output (2 pt.) relay 12-280VAC 5A

- Discrete output (2 pt.) relay 0-60VDC 5A
- Discrete output (2 pt.) relay 0-60VDC 10A
- Analog input (4 pt.) 4-20mA

Telemetry Modules

- RS-232 Module, DB9, DCE
- RS-485 Module

Memory Module

- 48K Memory module

[0048] If the collector is not within range, the data is forwarded to another collector associated with a location closer to the control center or a substation meter, to an intermediate collector, to be forwarded to the control center or substation. In essence, the network structure turns every collector into an individual network node capable of transmitting its respective meter indication data and meter indication data from either "nodes." Thus an embodiment of the present invention provides a self-healing network having minimal infrastructure that alleviates a line-of-site issue whereby a physical structure may block the transmission of an individual collector. An embodiment of the present invention also allows for scalability as the addition of a new collector at a new location is merely tantamount to adding an additional "node" to the network. In an implementation, however, the network node level between the various nodes and either the control center or a substation can be limited to a preselected number, such as 15. The system provides for both passive and dynamic execution of a meter read. In an embodiment, the collector sends a current read to the control center every 15 minutes, although the control center can prompt for an additional read if greater than 15 minutes delay accuracy is required.

[0049] The system control center further includes at least one computer, e.g., a server, including a processor to store, process, and manipulate data gathered by the collectors and transmitted to the remote control center. The control system correspondingly includes at least one data storage medium to provide for meter record storage and retrieval. The data storage medium is adapted to interface with software for storing and updating a database (the database includes a table(s) to assign the at least one collector physical address and assign various usage data). The usage data is compared to a temporal usage rate to formulate and store with the meter data to a record of consumption totals.

[0050] The computer system also provides various functions of the utility's control center with the meter data. For a billing office, for example, accurate timely data insures efficient monthly consumption billing on a customer-requested date. For a customer service department,

for example, the collection of daily metering data enables the utility to efficiently manage final reads and switching as well as customer complaints without the expense of dispatching someone to the field to re-read the meter. For a scheduling department, daily reads on all the meters in the service territory significantly improves load-forecasting accuracy. For a loss management department, the collection of tamper status information on a daily basis enables quick identification and resolution of energy theft. For a marketing department, for example, daily reads allow targeting and delivery of new rates or selectable billing dates to specific customers. Daily reads on a customer that has multiple meters in multiple locations also enables delivery of aggregated billing service, or same-day billing services for all its locations. For an engineering/distribution planning department, daily data collection provides an accurate, continually updated picture of daily load that can be isolated to a specific area, enabling optimum efficiency and system planning, outage management, equipment installation, and maintenance. Additionally, frequent data collection of actual usage can be compared to estimating usage, which enables quick and efficient reconciliation and settlements between utilities, generators, energy service providers (ESPs), and power exchanges. For an end customer, access to daily usage information increases customer satisfaction by enabling more efficient management of energy usage and predicting energy expenditures more accurately.

[0051] An embodiment of the system and system software provides for a customer an increased understanding of its usage patterns. This understanding enables the proper selection of rate options, supplier choices, aggregation and bulk purchasing opportunities and efficient forecasting and settlements. The system also advantageously provides for power outage notification and restoration notification. Additionally, the system provides for billing options such as selectable billing dates, selectable billing frequencies, and on-demand billing, which are not cost-efficient when using manual reading of the meter.

[0052] An embodiment of the system and system software provides for the utility increased distribution effectiveness including improved facilities and infrastructure planning, maintenance improvements, improved system reliability, operational efficiencies, improved customer service, outage detection, forecasting and settlements, and load balancing and planning. The system software also advantageously provides for data warehousing and data mining, historical patterns and expectations analysis, analysis for new rates structures, and services bundling such as

aggregation of billing to an individual customer, outage detection monitoring, and Internet access to the data.

[0053] An embodiment of the system and system software additionally benefit the utility by providing cost savings on regular "on-cycle" meter readings, the ability to obtain more easily (instantly) final meter reads for opening/closing accounts, streamlined high bill investigations, the ability to flag potential high consumption before consumers get a high bill, help in pinpointing system losses and detect theft in service. Additionally, the system and system software also advantageously enable more frequent reads with minimal incremental cost, enable custom billing dates, support customized rates for large customers, provide detailed consumption information to customers to provide watchdog services, like leakage monitoring, improved cash flow management due to a reduction in bill contests, improved revenue forecasting by tying detailed consumption information to production data and expected billings, enable more sophisticated rates, and reduce billing adjustments.

[0054] The system and system software of the present invention also provide for reduced capital costs due to the reduced number of vehicles necessary to physically service the meters, labor savings including the reduction in staff hours for meter reading and meter reading-related customer service, savings on vehicles and miscellaneous costs associated with meter reading, and provide for increased revenues from reducing system losses or replacing older inaccurate meters. Also, an embodiment of a system provides the utility company with the ability for "back-end" billing and accounting software to bundle with the collector and associated system software to provide a gathering, transmission, billing, collection and reporting solution.

[0055] In the preferred embodiment of the present invention, the network software associated with a server and associated with each collector in the system can include a preselected protocol, such as an application layer protocol positioned at level 7 of an OSI model as understood by those skilled in the art, which provides communication between devices connected on different types of buses or networks. This software, for example, can allow collectors to communicate with each other and a server or substation. The preselected protocol can be a request/reply protocol and offers services specified by message type.

[0056] A preselected protocol message packet is built by a master application that initiates a preselected transaction. The message type indicates to the slave application what kind of action to perform. The size of the preselected protocol message packet is device dependent and can

have a maximum of 256 bytes. In an embodiment, the preselected protocol uses a focused representation for addresses and data items. This focus, for example, can occur such as when a numerical quantity larger than a single byte is transmitted, the most significant byte is sent first.

[0057] The preselected protocol includes a non-routed protocol frame and a routed protocol frame. In an embodiment, the routed protocol frame includes the following elements: a Start of Message (SOT), Message Type (MT), Message Sequence Number (MSN), Message Length (ML), Message Date Time (MDT), Routing Source Node Information (RSN), Routing Source Node Identification (RSID), Routing Subnet Mask (RSM), Routing Destination Node Identification (RDID), Routing Gateway Information (RGI) or Routing Gateway Number (RGN), Routing Gateway Index (RGI), Routing Gateway Node Identification (RGID), Payload Data (PD), and Cyclical Redundancy Check (CRC).

SOT	MT	MSN	ML	MDT	RSN	RSID	RSM	RDID	RGI	RGID	PD	CRC
-----	----	-----	----	-----	-----	------	-----	------	-----	------	----	-----

[0058] The non-routed protocol frame is nearly identical except for does not include the RGID.

SOT	MT	MSN	ML	MDT	RSN	RSID	RSM	RDID	RGI	PD	CRC
-----	----	-----	----	-----	-----	------	-----	------	-----	----	-----

[0059] The following have an example of the Protocol Frame Element Definitions:

Element	Description	Length	Range	Comments
SOT	Start of Transmission	1 byte	[0xEE]	Constant Value
MT	Message Type	1 byte		See below
MSN	Message Sequence Number	1 byte	[0x00—0xFF]	Message originator connection dependent incremental message identification number.
ML	Message Length	1 byte	[0x00—0xFF]	Device Dependent
MDT	Message Date Time	4 bytes	[0x00000000—0xFFFFFFFF]	Message Date Time Stamp
RSN	Routing Source Node Information	1 byte		<i>Reserved for future use.</i>
RSID	Routing Source Node Identification	4 bytes	[0x00000000—0xFFFFFFFF]	Message originator unique unsigned long identification number.
RSM	Routing Subnet Mask	4 bytes	[0x00000000—0xFFFFFFFF]	Message filtering mask
RDID	Routing Destination Node Identification	4 bytes	[0x00000000—0xFFFFFFFF]	Message destination unique unsigned long identification number.

Element	Description	Length	Range	Comments
RGI	Routing Gateway Information	1 byte	[0x00—0xFF]	High nibble RGN. Low nibble RGI.
RGN	Routing Gateway Number	4 bits	[0x00—0x0F]	Number of Routing Gateways required transmitting message from source node to destination node.
RGI	Routing Gateway Index	4 bits	[0x00—0x0F]	Current Routing Gateway index while transmitting message from source node to destination node.
RGID	Routing Gateway Node Identifications	4 bytes * RGN		Routing Source Identification Number of each Routing Gateway along path from source node to destination node.
PD	Payload Data			Payload Data is dependent upon message type.
CRC	Cyclical Redundancy Check	2 bytes	[0x00—0xFF]	CRC-16 Polynomial Mask 0x1021

[0060] According to an embodiment, the preselected protocol can support three levels of message security. Each security level is validated by an up to eight-byte security password. Each security level password byte may be any ASCII character. Each security level password is stored relevant to the routing source identification number. For the purpose of CRC calculation only, the security level password is appended to the message.

[0061] In this embodiment, the preselected protocol frame Message Type element is a bit-significant field and includes the following elements: Security Level (SL), Message Type (MT), Read or Write Direction Flag (R#/W), and Acknowledgement Flags (ACK).

SL	MT	R#/W	ACK
----	----	------	-----

The following are an example of Message Type Byte Element Definitions:

Element	Description	Length	Range	Comments
SL	Security Level	2 bits	[0x00—0x03]	0x00: None 0x01: Security Level 1 0x02: Security Level 2 0x03: Security Level 3
MT	Message Type	3 bits	[0x00—0x07]	<i>See section 3.2: Message Type Definition</i>
R#/W	Read or Write Direction Flag	1 bit	[0x00—0x01]	0x00: Read 0x01: Write
ACK	Acknowledgement Flags	2 bits	[0x00—0x03]	0x00: Send/Negative Acknowledge 0x01: Acknowledge Send 0x02: Response 0x03: Acknowledge Response

[0062] In an embodiment, when a master application directly addresses a slave application (non-routing), the slave application processes the message type specified action and responds by setting the acknowledge binary code to ‘Response’ (0x02) within the message type frame element. When a master application addresses a slave application via routing, the first gateway node will route the message to the next gateway node and respond to the master application by setting the acknowledge binary code to ‘Ack Send’ (0x01) within the message type frame element. When the destination node receives the routed message, the destination node processes the message type specified action and responds by setting the acknowledge binary code to ‘Response’ (0x02) within the message type frame element. If the message fails to respond from the destination node, the gateway node of last transmission will originate and route the return message to the source node by setting the acknowledge binary code to ‘Send / Negative Acknowledge’ (0x00) within the message type frame element.

[0063] In an embodiment, the following preselected protocol message types, for example, can be supported:

Message Type	Message Type Description	Read Supported	Write Supported	Security Level
0x00	Control	Yes	Yes	0x00—0x03
0x01	Control Route	Yes	Yes	0x00—0x03
0x02	Control Broadcast	Yes	Yes	0x00—0x03
0x03	<i>Reserved</i>	-	-	-
0x04	Configuration	Yes	Yes	0x02—0x03
0x05	<i>Reserved</i>	-	-	-

Message Type	Message Type Description	Read Supported	Write Supported	Security Level
0x06	1 ² C	Yes	Yes	0x03
0x07	Diagnostic	Yes	No	0x03

[0064] The preselected protocol frame element includes a payload data section. The payload data section of the message packet sent from master application to slave application contains information that the master application uses to take the action defined by the message type. The payload data section of the message packet may be nonexistent (of zero length) in certain kinds of requests. In such case the slave application does not require any additional information. The message type in this instance specifies the action. The following details the payload data requirements for each of the supported message types. Data registers are referenced by control type and control index. For example: To reference the first analog input point the control type would be 0x02 and the control index would be 0x00.

Examples of Control Data Types are as follows:

Control Data Type	Control Description	Data Type	Data Range
0x00	Discrete Input	Byte	[0x00—0x01]
0x01	Discrete Output	Byte	[0x00—0x01]
0x02	Analog Input	Unsigned Integer	[0x00—0xFFFF]
0x03	Analog Output	Unsigned Integer	[0x00—0xFFFF]
0x04	Date Time	<i>See below</i>	
0x05	Counter	Unsigned Log	[0x00—0xFFFFFFFF]
0x06	<i>Reserved</i>		
0x08	<i>Reserved</i>		
0x09	<i>Reserved</i>		
0x10	History Record	<i>See below</i>	
0x11	Event Record	<i>See below</i>	

[0065] Discrete Control Data Types 0x00 and 0x01 are packed into bytes. As understood by those skilled in the art, a master query must divide the requested point index by 0x08 to obtain the proper control data index. For example: A master query for the status of discrete input 0x09 must request control data type 0x00 and index 0x01. The slave response data value bit 1 will contain the status of discrete input 0x09.

[0066] The most significant bit of the Control Data Type is an exception response flag. For example: if a control message requests an index that is not supported by the slave device, the slave device response will echo the requested data type and set the most significant bit. The byte

following the control index will be a single byte Control exception code regardless of data type. Control exception codes are defined below. The Control Date Time data type can be defined as the number of seconds from the host server reference date and time. The Control History Record data type is defined as the following:

Offset	Description	Control Data Type	Data Type	Comment
0x00	Data Time Stamp	Control Date Time	Unsigned Long	Control date time stamp of stored data value
0x04	Data Value Type	Control Data Type	Byte	Control data type of stored data value
0x05	Data Value	Control Data Value	-	Control Data value

[0067] The Control Event Record data type can be defined as the following:

Offset	Description	Control Data Type	Data Type	Comment
0x00	Data Time Stamp	Control Date Time	Unsigned Long	Control date time stamp of stored data value
0x04	Event Type Code	Event Type	Byte	Event Type Code Reserved Always 0x00.
0x05	Data Value Type	Control Data Type	Byte	Control data type of stored data value
0x06	Data Old Value	Control Data Old Value	-	Control data old value
-	Data New Value	Control Data New Value	-	Control data new value

[0068] The Control exception codes can include the following:

Control Exception Codes		
Code	Name	Meaning
0x00	ILLEGAL FUNCTION	The requested operation to perform on the referenced data type is not support by the end device or not permitted due to security level access.
0x01	ILLEGAL DATA TYPE	The data type received in the query is not an allowable type for the slave device.
0x02	ILLEGAL DATA INDEX	The data index received in the query is not an allowable index for the slave device.
0x03	ILLEGAL DATA VALUE	The value contained in the query data field is not an allowable value for the slave device.

Control Exception Codes		
Code	Name	Meaning
0x04	SLAVE DEVICE BUSY	The slave device is engaged in processing a long-duration program command. The master device should retransmit the message later when the slave device is free.
0x05	SLAVE DEVICE FAILURE	An unrecoverable error occurred while the slave device was attempting to perform the requested action.

[0069] As shown in FIGS. 6-7, in an embodiment, the control message type includes a control read and a control write message type. The control read message type is used to read data registers from a slave device. Read access to data registers is dependent upon security level as defined as follows:

Control Data Type	Control Description	Data Type	Security Levels
0x00	Discrete Input	Byte	0x00—0x03
0x01	Discrete Input	Byte	0x00—0x03
0x02	Analog Input	Unsigned Integer	0x00—0x03
0x03	Analog Output	Unsigned Integer	0x00—0x03
0x04	Date Time	<i>See above</i>	0x02—0x03
0x05	Counter	Unsigned Long	0x01—0x03
0x06	<i>Reserved</i>	-	-
0x07	<i>Reserved</i>	-	-
0x08	<i>Reserved</i>	-	-
0x09	History Record	<i>See above</i>	0x01—0x03
0x10	Event Record	<i>See above</i>	0x01—0x03

[0070] In an embodiment, the payload data element of the control read message frame includes a master and a slave. The master can include the elements of:

COUNT _N	CT ₁	CI ₁	...	CT _N	CI _N
--------------------	-----------------	-----------------	-----	-----------------	-----------------

where for each requested data value N, the control read message from the master must designate the control data type and control data index.

[0071] The slave can include the elements of:

COUNT _N	CT ₁	CI ₁	CV ₁	...	CT _N	CI _N	CV _N
--------------------	-----------------	-----------------	-----------------	-----	-----------------	-----------------	-----------------

where for each requested data value N, the control read message response from the slave must designate the control data type, control data index, and control data value.

Element	Description	Length	Range	Comments
COUNT _N	Point Quantity	1 byte	[0x00—0xFF]	Slave Device Message Length Dependent
CT ₁	Control Data Type	1 byte		<i>See above</i>
CI ₁	Control Data Index	1 byte	[0x00—0xFF]	Slave Device Dependent
CV ₁	Control Data Value			<i>See above</i>

[0072] In this embodiment, the control write message type is used to write values to data registers in a slave device. Write access to data registers is dependent upon security level as defined as follows:

Control Data Type	Control Description	Data Type	Security Levels
0x00	Discrete Input	Byte	Exception Code 0x00
0x01	Discrete Output	Byte	0x01—0x03
0x02	Analog Input	Unsigned Integer	Exception Code 0x00
0x03	Analog Output	Unsigned Integer	0x01—0x03
0x04	Date Time	<i>See Control Date Time structure definition</i>	0x02—0x03
0x05	Counter	Unsigned Long	0x02—0x03
0x06	<i>Reserved</i>		
0x07	<i>Reserved</i>		
0x08	<i>Reserved</i>		
0x09	History Record	<i>See Control History Record structure definition</i>	Exception Code 0x00
0x10	Event Record	<i>See Control Event Record structure definition</i>	Exception Code 0x00

[0073] As shown in FIGS. 6-7, in an embodiment, the payload data element of the control write message frame includes a master and a slave. The master can include the elements of:

COUNT _N	CT ₁	CI ₁	CV ₁	...	CT _N	CI _N	CV ₁
--------------------	-----------------	-----------------	-----------------	-----	-----------------	-----------------	-----------------

where for each requested data value N, the control write message from the master must designate the control data type, control data index, and control data value.

[0074] The slave can include the elements of:

COUNT _N	CT ₁	CI ₁	...	CT _N	CI _N
--------------------	-----------------	-----------------	-----	-----------------	-----------------

where for each requested data value N, the control write message response from the slave must acknowledge the control data type and control data index.

Element	Description	Length	Range	Comments
COUNT _N	Point Quantity	1 byte	[0x00—0xFF]	Slave Device Message Length Dependent
CT ₁	Control Data Type	1 byte	<i>See above: Control Data Types</i>	
CI ₁	Control Data Index	1 byte	[0x00—0xFF]	Slave Device Dependent
CV ₁	Control Data Value		<i>See above: Control Data Types</i>	

[0075] This embodiment includes a Control Route message type, defined for increased efficiency of network bandwidth by allowing the collection of intermediate routing gateway data while acquiring end node data. Data types, exception codes, and security codes for the Control Route message types are defined with the Control message type.

[0076] The Control Route message type includes a Control Route Read and a Control Route Write message type. The control route read message type is used to read data registers from a slave device and each routing gateway node.

[0077] The payload data element of the control route read message frame also includes a master and a slave. The master can include the elements of:

COUNT _N	CT ₁	CI ₁	...	CT _N	CI _N
--------------------	-----------------	-----------------	-----	-----------------	-----------------

where for each requested data value N, the control read message from the master must designate the control data type and control data index.

[0078] The slave can include the elements of:

COUNT _{N*X}	CT ₁	CI ₁	CV ₁	...	CT ₁₁	CI ₁₁	CV ₁₁	...	CT _{NX}	CI _{NX}	CV _{NX}
----------------------	-----------------	-----------------	-----------------	-----	------------------	------------------	------------------	-----	------------------	------------------	------------------

where for each requested data value N, the control read message response from the slave (and each routing gateway node X) must designate the control data type, control data index, and control data value.

Element	Description	Length	Range	Comments
COUNT _N	Point Quantity	1 byte	[0x00—0Xff]	Device Message Length Dependent
CT ₁	Control Data Type	1 byte	<i>See above: Control Data Types</i>	
CI _{IX}	Control Data Type	1 byte	Control Data Type for routing gateway node X	
CI ₁	Control Data Index	1 byte	[0x00—0xFF]	Device Dependent
CV ₁	Control Data Value		<i>See above: Control Data Types</i>	

[0079] The control route write message type is used to write data registers from a slave device and each routing gateway node.

[0080] The payload data element of the control route write message frame includes a master and a slave. The master can include the elements of:

COUNT _N	CT ₁	CI ₁	CV ₁	...	CT _N	CI _N	CV ₁
--------------------	-----------------	-----------------	-----------------	-----	-----------------	-----------------	-----------------

where for each requested data value N, the control route write message from the master must designate the control data type, control data index, and control data value.

[0081] The slave can include the elements of:

COUNT _{N*(X+1)}	CT ₁	CI ₁	...	CT ₁₁	CI ₁₁	...	CT _{N1}	CI _{N1}	CT _{1X}	CI _{1X}	...	CT _{NX}	CI _{NX}
--------------------------	-----------------	-----------------	-----	------------------	------------------	-----	------------------	------------------	------------------	------------------	-----	------------------	------------------

where for each requested data value N the control write message response from the slave (and each routing gateway node X) must acknowledge the control data type and control data index.

Element	Description	Length	Range	Comments
COUNT _N	Point Quantity	1 byte	[0x00—0xFF]	Device Message Length Dependent
CT ₁	Control Data Type	1 byte	<i>See section 4.1.1: Control Data Types</i>	
CI _{1X}	Control Data Type	1 byte	Control Data Type for routing gateway node X	
CI ₁	Control Data Index	1 byte	[0x00—0xFF]	Device Dependent
CV ₁	Control Data Value	<i>See section 4.1.1: Control Data Types</i>		

[0082] An embodiment can include a Control Broadcast message type. The Control Broadcast Message Type is defined for increased efficiency of network bandwidth by allowing the collection/control of multiple end node devices. Data types, exception codes, and security codes for the Control Route message types are defined with the Control message type.

[0083] The Control Broadcast command may be routed through the network and will be transmitted from the device identified by the routing destination identification number field. When the device identified by the routing destination identification number transmits the control broadcast message, the device will use a routing destination identification number of 0x00000000. If the routing destination identification number is unknown, a routing destination identification number of 0x00000000 may be used if the routing gateway information field is 0x00.

[0084] The Control Broadcast Message Type includes a Control Broadcast Read Message Type and a Control Broadcast Write Message Type. The Control Broadcast Read Message type is used to read data registers from multiple slave devices. Slave nodes to respond to specified action are determined by the routing subnet mask.

[0085] The payload data element of the control broadcast read message frame includes a master and a slave. The master can include the elements of:

COUNT _N	CT ₁	CI ₁	...	CT _N	CI _N
--------------------	-----------------	-----------------	-----	-----------------	-----------------

where for each requested data value N, the control broadcast message from the master must designate the control data type and control data index.

[0086] The slave can include the elements of:

COUNT _N	CT ₁	CI ₁	CV ₁	...	CT _N	CI _N	CV _N
--------------------	-----------------	-----------------	-----------------	-----	-----------------	-----------------	-----------------

where for each requested data value N, the control broadcast message response from each slave must designate the control data type, control data index, and control data value.

[0087] The control broadcast write message type is used to write values to data registers in multiple slave device nodes. Slave nodes to perform specified action are determined by the routing subnet mask.

[0088] The payload data element of the control broadcast write message frame includes a master and a slave. The master can include the elements of:

COUNT _N	CT ₁	CI ₁	CV ₁	...	CT _N	CI _N	CV ₁
--------------------	-----------------	-----------------	-----------------	-----	-----------------	-----------------	-----------------

where for each requested data value N, the control broadcast write message from the master must designate the control data type, control data index, and control data value.

[0089] The slave can include the elements of:

COUNT _N	CT ₁	CI ₁	...	CT _N	CI _N
--------------------	-----------------	-----------------	-----	-----------------	-----------------

where for each requested data value N the control broadcast write message response from the slave (primary only) must acknowledge the control data type and control data index.

[0090] Embodiments of the present invention also provides an automated meter reading network system having a plurality of utility meters each one positioned remote from the other ones of the plurality of utility meters, a plurality of sensors interfaced with each of the plurality of meters so that at least one of the plurality of sensors interfaces with and is positioned adjacent at least one of the plurality of meters to thereby sense utility usage data from each of the plurality of meters, a communication network, a plurality of meter data collectors positioned to collect utility usage data from each of the plurality of sensors so that at least one of the plurality of meter data collectors is positioned adjacent at least one of the plurality of utility meters and in communication with at least one of the plurality of sensors which interfaces with the at least one of the plurality of utility meters, the plurality of meter data collectors also being adapted to be positioned in communication with each other through the communication network so that each of

the plurality of meter data collectors defines a communication node in the communication network and the plurality of meter data collectors defines a plurality of communication nodes in the network, and a host computer positioned remote from the plurality of meter data collectors at a utility central station and in communication with each of the plurality of communication nodes in the communication network so that each one of the plurality of communication nodes are adapted to communicate with other ones of the plurality of communication nodes in the communication network to thereby reduce line-of-site communication problems between each of the plurality of communication nodes and the host computer.

[0091] Additionally, the system can also have each of the plurality of meter data collectors including a collector transceiver positioned to transmit data to the host computer and to other ones of the plurality of meter data collectors through the communication network and to receive data from the computer and from the other ones of the plurality of meter data collectors through the communication network and a collector controller positioned to control collecting of utility usage data and the transmitting and receiving of data to and from the collector transceiver. The host computer, for example, can include a host transceiver positioned to transmit data to and receive data from each of the plurality of communication nodes and a host controller positioned to control collecting of utility usage data from each of the plurality of communication nodes, transmitting data to each of the plurality of communication nodes through the host transceiver, and receiving data from each of the plurality of communication nodes through the host transceiver. Each collector controller of the plurality of meter data collectors and the host controller can include controller software associated with the controller and having a network data communication protocol. The network data communication protocol includes a preselected application layer, and the communication network comprises a radio frequency communication network. The radio frequency communication network has a frequency acceptable to the Federal Communication Commission or other regulatory agency as desired. For example, the frequency can be in the range of 850-1000 mega-hertz or 2.4-5.8 giga-hertz. The frequency CAN advantageously continuously change between a plurality of different preselected frequencies to thereby define frequency hopping. The controller software of the host controller initiates polling of the plurality of communication nodes through the frequency hopping within the communications network, and each of the plurality of communication nodes responds to the polling by the host computer through the frequency hopping within the communications

network. The network software includes an autosequencer to initiate polling of the plurality of communication nodes whereby each of the plurality of communication nodes is individually attempted to be polled by the host computer to determine a strength of communication signal between the host computer and each of the plurality of communication nodes. Each of the plurality of communication nodes also attempt to communicate with each other responsive to the autosequencer to determine a strength of communication signal between one of the plurality of communications nodes and another one of the plurality of communication nodes, and the autosequencer further determines a communication sequence to each of the plurality of communication nodes responsive to the strength of communication signal between the host computer and each of the plurality of communication nodes and responsive to the strength of communication signal between each of the plurality of communication nodes to define a preferred communication sequence path to each of the plurality of communication nodes from the host computer. The autosequencer updates the preferred communication sequence path to allow the preferred communication sequence path to vary over time.

[0092] The plurality of meter data collectors, for example, can include a first meter data collector, a second meter data collector in communication with the first meter data collector, and a third meter data collector in communication with at least one of the first and second meter data collectors. The first meter data collector can be positioned remote from the host computer to thereby have a greater signal strength than the second meter data collector and the third meter data collector. The second meter data collector can be positioned remote from host computer to thereby have a greater signal strength than the third meter data collector, and the network software further includes a raking router to collect meter usage data from the first meter data collector responsive to polling received from the host computer and to rakingly collect data from each of the second and third meter data collectors responsive to the polling so that meter usage data is collected from each of the first, second, and third meter data collectors responsive to polling the first meter data collector and routed to the host computer.

[0093] At least one of the plurality of meter data collectors is positioned within at least one of the following: the same housing as at least one of the plurality of utility meters, a separate housing positioned closely adjacent at least one of the plurality of utility meters, and a separate housing positioned closely adjacent a subset of the plurality of utility meters. The host computer further includes memory having a meter data collector database associated therewith to thereby

store meter collector data associated with each of the plurality of meter data collectors, the meter collector data including collector identification, collector physical address, and strength of signal between CIDs.

[0094] Also, an automated meter reading network system is provided according to an embodiment of the present invention. The system includes a plurality of sensors adapted to be interfaced with each of a plurality of utility meters each positioned remote from another one of the plurality of utility meters so that at least one of the plurality of sensors interfaces with and is positioned adjacent at least one of the plurality of meters to thereby sense utility usage data from each of the plurality of meters, and a plurality of meter data collectors positioned to collect utility usage data from each of the plurality of sensors so that at least one of the plurality of meter data collectors is positioned in communication with at least one of the plurality of sensors. The plurality of meter data collectors also is adapted to be positioned in communication with each other through the communication network so that each of the plurality of meter data collectors defines one of a plurality of communication nodes in a communication network, and a host computer is positioned remote from the plurality of meter data collectors and in communication with each of the plurality of communication nodes so that each one of the plurality of communication nodes are adapted to communicate with other ones of the plurality of communication nodes.

[0095] The system can also have each of the plurality of meter data collectors including a collector transceiver positioned to transmit data to the host computer and to other ones of the plurality of meter data collectors and to receive data from the computer and from the other ones of the plurality of meter data collectors and a collector controller positioned to control collecting of utility usage data and the transmitting and receiving of data to and from the collector transceiver. The host computer includes a host transceiver positioned to transmit data to and receive data from each of the plurality of communication nodes and a host controller positioned to control collecting of utility usage data from each of the plurality of communication nodes, transmitting data to each of the plurality of communication nodes through the host transceiver, and receiving data from each of the plurality of communication nodes through the host transceiver. Each collector controller of the plurality of meter data collectors and the host controller include controller software associated with the controller and having a network data communication protocol, the network data communication protocol includes a preselected

application layer, and the communication network includes a radio frequency communication network.

[0096] The radio frequency communication network has a frequency in the range of 850-1000 mega-hertz, wherein the frequency continuously changes between a plurality of different preselected frequencies to thereby define frequency hopping, wherein the controller software of the host controller initiates polling of the plurality of communication nodes through the frequency hopping within the communications network, and wherein each of the plurality of communication nodes responds to the polling by the host computer through the frequency hopping within the communications network.

[0097] The network software includes an autosequencer to initiate polling of the plurality of communication nodes whereby each of the plurality of communication nodes is individually attempted to be polled by the host computer to determine a strength of communication signal between the host computer and each of the plurality of communication nodes, wherein each of the plurality of communication nodes also attempt to communicate with each other responsive to the autosequencer to determine a strength of communication signal between one of the plurality of communications nodes and another one of the plurality of communication nodes, and wherein the autosequencer further determines a communication sequence to each of the plurality of communication nodes responsive to the strength of communication signal between the host computer and each of the plurality of communication nodes and responsive to the strength of communication signal between each of the plurality of communication nodes to define a preferred communication sequence path to each of the plurality of communication nodes from the host computer. The autosequencer updates the preferred communication sequence path to allow the preferred communication sequence path to vary over time.

[0098] The plurality of meter data collectors can include a first meter data collector, a second meter data collector in communication with the first meter data collector, and a third meter data collector in communication with at least one of the first and second meter data collectors, wherein the first meter data collector is positioned remote from the host computer to thereby have a greater signal strength than the second meter data collector and the third meter data collector, wherein the second meter data collector is positioned remote from host computer to thereby have a greater signal strength than the third meter data collector, and wherein the network software further includes a raking router to collect meter usage data from the first meter

data collector responsive to polling received from the host computer and to rakingly collect data from each of the second and third meter data collectors responsive to the polling so that meter usage data is collected from each of the first, second, and third meter data collectors responsive to polling the first meter data collector and routed to the host computer. At least one of the plurality of meter data collector is positioned within at least one of the following: the same housing as at least one of the plurality of utility meters, a separate housing positioned closely adjacent at least one of the plurality of utility meters, and a separate housing positioned closely adjacent a subset of the plurality of utility meters. The host computer further includes a memory having a meter data collector database associated therewith to thereby store meter collector data associated with each of the plurality of meter data collectors, the meter collector data including collector identification, collector physical address, and strength of signal between meter data collectors.

[0099] An embodiment of the present invention also provides a meter data collector to interface with a utility meter. The meter data collector includes a stationary housing adapted to be mounted adjacent a utility meter, a sensor positioned to sense meter usage data from the utility meter, a high power transceiver associated with the housing to transmit meter usage data from the meter data collector and to receive communication remote from the stationary housing in a medium to high range, a collector controller positioned within the housing to control data communication to and from the high power transceiver and to control collecting of meter usage data from the sensor responsive to a remote command, and a memory positioned within the stationary housing and associated with and in communication with the controller to store data therein, the memory including network software to communicate the meter usage data remotely through a communication network. The network software can include a preselected network data communication protocol, which includes a preselected application layer, and the communication network can be a radio frequency communication network. The radio frequency communication network can have a frequency in the range acceptable to the FCC such as 850-1000 mega-hertz or 2.4 to 5.8 giga-hertz and which allows the frequency to continuously change between a plurality of different preselected frequencies to thereby define frequency hopping. A remote host computer controller can initiate polling of the meter data collector through the frequency hopping within the communications network, and the collector controller responds to

the polling by the host computer controller through the frequency hopping within the communications network.

[00100] The network software includes an autosequencer to initiate respond to polling by the host computer controller and to initiate polling of at least one of a plurality of communication nodes whereby each of the plurality of communication nodes is individually attempted to be polled by the host computer to determine a strength of communication signal between the host computer and each of the plurality of communication nodes, and wherein each of the plurality of communication nodes also attempt to communicate with each other responsive to the autosequencer to determine a strength of communication signal between one of the plurality of communications nodes and another one of the plurality of communication nodes to thereby assist in determining a preferred communication sequence path to each of the plurality of communication nodes from the host computer. The autosequencer updates the preferred communication sequence path to allow the preferred communication sequence path to vary over time.

[00101] As shown in FIGS. 1-15E, as described above, the present invention also includes various embodiments of related methods. An embodiment of a method of collecting utility meter usage data includes sensing meter usage data from each of a plurality of utility meters positioned remote from each other, collecting utility usage data by each of a plurality of meter data collectors positioned adjacent each of the plurality of utility meters, determining a preferred polling sequence route responsive to the strength of communication signal, polling each of the plurality of meter data collectors by a host computer positioned remote from the plurality of meter data collectors to thereby determine a strength of communication signal between the remote host computer and the plurality of meter data collectors positioned adjacent the plurality of utility meters, and transmitting meter usage data to the host computer from each of the plurality of meter data collectors along the preferred polling sequence route responsive to the polling by the host computer. The steps of polling and determining, for example, are periodically performed to update the preferred polling sequence route over time. The plurality of meter data collectors can include a first meter data collector, a second meter data collector in communication with the first meter data collector, and a third meter data collector in communication with at least one of the first and second meter data collectors, and the first meter data collector is positioned remote from the host computer to thereby have a greater signal

strength than the second meter data collector and the third meter data collector, the second meter data collector is positioned remote from host computer to thereby have a greater signal strength than the third meter data collector, and the method can further include rakingly collecting data from each of the second and third meter data collectors responsive to the polling of the first meter data collector so that meter usage data is collected from each of the first, second, and third meter data collectors responsive to polling the first meter data collector and routing the rakingly collected meter usage data to the host computer.

[00102] At least one of the plurality of meter data collector is positioned within at least one of the following: the same housing as at least one of the plurality of utility meters, a separate housing positioned closely adjacent at least one of the plurality of utility meters, and a separate housing positioned closely adjacent a subset of the plurality of utility meters. The host computer can include a memory having a meter data collector database associated therewith to thereby store meter collector data associated with each of the plurality of meter data collectors, the meter collector data including collector identification, collector physical address, and strength of signal between meter data collectors.

[00103] An embodiment of the present invention also provides a method of monitoring a utility meter mounted to a building. The method includes mounting a meter data collector defining a remote collection unit adjacent a utility meter mounted to a building, collecting meter data from the utility meter by the remote collection unit, transmitting the meter data to a router of a communication network service provider, transmitting the meter data through a communication network associated with the communication network service provider, and receiving the meter data from the communication network by a computer device. The remote collection unit can be a first remote collection unit, the utility meter can be a first utility meter, and the building can be a first building, and the method further can include mounting a second remote collection unit adjacent a second utility meter mounted to second building, collecting meter data from the second utility meter by the second remote collection unit and transmitting the meter data from the second utility meter by the second remote collection unit, and transmitting the meter data of the second utility meter to the first remote collection unit. The meter data transmitted to the router, for example, can include meter data from the first and second remote collection units.

[00104] Yet another embodiment of a method of collecting utility meter data from a plurality of utility meters each mounted to a different building and each in communication with a

respective one of a plurality of meter data collectors defining a plurality of remote collection units is also provided. The method can include transmitting utility meter data from a first remote collection unit of the plurality of utility of remote collection units to a second remote collection unit of the plurality of collection units, and transmitting utility meter data of the first remote collection unit and utility meter data of the second remote collection unit from the second remote collection unit to a host computer. The method can also include transmitting meter data from a third remote collection unit to the first remote collection unit and wherein the utility meter data of the first remote collection unit includes utility meter data from the third remote collection unit.

[00105] Another embodiment of a method of collecting utility meter data includes positioning a meter data collector defining a remote collection unit having bi-directional RF data communication within a housing having a glass facing on at least one side thereof, collecting utility meter data by the remote collection unit positioned adjacent the housing, polling the remote collection unit from a host computer by RF data communication through the glass facing, and transmitting the collected utility meter data from the remote collection unit through the glass facing to the host computer responsive to the polling. The utility meter can include a first utility meter of a plurality of utility meters, and the first utility meter can be one or more of a gas utility meter, an electric utility meter, and a water meter. A second of the plurality of utility meters can be a different one of a gas utility meter, an electric utility meter, and a water utility meter. The step of collecting includes collecting utility meter data from both the first and second utility meters by the remote collection unit.

[00106] Still another embodiment of a method of collecting utility meter data includes positioning a plurality of meter data collectors defining a plurality of remote collection units adjacent to respective one of a plurality of utility meters. Each of the plurality of utility meters is mounted to a different building. The method also includes polling each of the plurality of remote collection units from a collection computer positioned remote from the plurality of remote collection units and transmitting meter data from each of the plurality of remote collection units to the collection computer responsive to the polling. The method can also include the collection computer being a field collection unit such as another remote collection unit or the collection computer being a host computer. The method can further include a host computer positioned remote from and in communication with the field collection unit. The method additionally can include transmitting the utility meter data from the field collection unit to a router of a

communication network service provider, communicating the utility meter data through a communication network associated with the communication network service provider, and receiving the utility meter data by a host computer in communication with the communication network. The method still further can include a first remote collection unit of the plurality of remote collection units transmitting utility meter data to a second remote collection unit of the plurality of remote collection units, the second remote collection unit transmitting the utility meter data of the first and second remote collection units to a third remote collection unit of plurality of remote collection units, and the third remote collection unit transmitting utility meter data of the first, second, and third remote collection unit to the field collection unit.

[00107] For how each meter data collector defining a remote collection unit operates, the device hardware, e.g., silicon integrated circuit such as Dallas Semiconductor DS2401/DS2411, provides a 6-byte unique identification number. The least significant 4 bytes of the unique identification number are utilized to determine a selected routing source identification number. The least significant 1 byte of the selected routing source identification number determines the device default frequency index within the attached array of transmit and receive settings for a transceiver such as a Chipcon 1020 bi-directional transceiver as understood by those skilled in the art. For example, if the least significant byte of the selected routing source identification number were 0x00, then the corresponding default receive frequency would be 909300000 hertz (Hz). If the least significant byte of the selected routing source identification number were 0x001, then the corresponding default receive frequency would be 924200000 Hz. In this way, for example, 256 frequencies are utilized and organized in a pseudorandom non-repeating manner as illustrated in FIGS. 15A-15E.

[00108] As understood by those skilled in the art, the host computer, for example, can have server software to initiate communication messages to each of the plurality of destination remote collection units. A destination remote collection unit, for example, can be: (1) directly connected to the host computer; (2) connected via radio frequency from the remote collection unit directly connected to the host computer, or (3) connected via radio frequency for up to a preselected number, e.g., 15, radio frequency repeater remote collection units to the remote collection unit directly connected to the host computer. The communications portion of a message protocol packet can include the routing source identification number, routing source radio frequency index, routing destination identification number, routing destination radio frequency index,

routing gateway node count, and up to the preselected number, e.g., 15, routing gateway identification numbers and their corresponding radio frequency indices. The communications portion of the acknowledgement packet can include the routing identification number, routing source radio frequency index, routing destination identification number, and routing destination radio frequency index. The routing source identification number identifies the remote collection unit transmitting the message. The host server application, for example, can keep an internal database of the remote collection unit identification numbers and their active radio frequency indices based upon each successful communication. On startup, the host server application assigns the remote collection unit radio frequency index to the least significant byte of the unit unique address. The host server software, as understood by those skilled in the art, also can ensure non-consecutive identical frequency indices in any given communications path.

[00109] The message validation for the remote collection device can use a remote collection unit identification number to equal either the routing destination identification number or the first routing gateway identification number. The unit acknowledgment message validation can use the unit identification number to equal the routing destination identification number. Additional communication packet validation criteria include message sequence number, message type, and CRC calculations. Upon receipt of a valid message, the receiving remote collection unit will increment/alter its radio frequency index and transmit an acknowledge packet to the received packet routing source identification number at the current radio frequency index. If the remote collection unit device was the intended destination, then after transmitting the acknowledgment packet the remote collection unit will transmit the response at the incremented/alterd radio frequency index. If the remote collection unit was an intended receiver, but not the message destination (see, e.g., FIG. 5), after transmitting the acknowledgment packet the remote collection unit will forward the message utilizing the received packet first routing gateway frequency index. For example, the units configured as receivers can shift frequencies in synchronization with the units configured as transmitters as described above. The units, also for example, can use the same Chipcon 1020 bi-directional transceivers, or other transceivers as understood by those skilled in the art, and can be configured such that the remote collection unit receiver input bandwidth matches the hopping channel bandwidth of their corresponding remote collection unit transmitter.

[00110] This fixed automated meter reading network system 30 supports bi-directional communications with the capability of collection digital and analog input data, as well as functional control, via digital output relays. The remote collection unit platform monitors data, for example, from four digital inputs and two encoded inputs and transmits that data to a utility's central office via a 902-928 mega-hertz frequency hopping mesh network as understood by those skilled in the art. The remote collection unit 41, for example, utilizes a medium to high range RF radio capable of communications of 1600 meters or approximately one mile and a field host unit that connects the local area network to a wireless, cable, fiber, or telephony wide area network. Field host units (also which can be another remote collection unit) can reside at the municipality infrastructure level such as a sub-station, pump station, or municipal office. These intelligent units have an embodiment of the software of the present invention loaded and responsible for collecting interval data from the surrounding field 51 or remote 41 collection units then transmitting that data when requested by the primary host 61, located at the central office, in a batch format (see FIGS. 1-8).

[00111] After units are installed in the field and the primary host system 30 is in place, the software gathers a list of available field units. This process is dynamic in nature and at its conclusion would have a complete network communications map through a communication network 80 ready to begin the job of data collection. As a mesh network 80, each unit has multiple communication paths between it and the local field host unit 51, e.g., supporting up to 15 links or levels in a single path. The primary host system located at the central office, for example, polls field units on a revolving schedule 24 hours a day, 7 days a week, 365/366 days a year. Metering data received at the host site is then converted into OLE DB compatible database file formats, as understood by those skilled in the art, for input into existing customer information and billing systems. This system 30 and each remote collection unit 41, for example, allows for additional expansion of input/output as needed, including remote disconnect, appliance control for load curtailment, or outage detection to consumer value functions such as security, detection, or alarm notification. The system can have a primary host 61 located at a central office with connection capabilities to customer billing, a field host unit located through the city and connected to the fiber optic infrastructure to establish wireless communication to all available remote collection units. The field host units establish the communication, request and store data, and pass the instructions from the primary host to the remote collection units. The

remote collection units, located at the consumer such as mounted to residence 40 or other building structure, can each be connected to all devices at the consumers location that are required to meet the appropriate phase requirements, such as metering aspects in phase one, community service aspects in phase two, and so forth as understood by those skilled in the art. The remote collection units can collect metering data from the various meters, e.g., electric 72, water 74, gas 76, or other usage, the field host unit polls the consumer located at the remote collection unit, e.g., approximately every 15 minutes, and receives a packet of information that includes I.D., consumption, data and time stamp, network stats, and other data as desired. The field host unit can maintain a file of all collected data received from each remote collection unit in its range. The primary host 61 establishes a connection with each field host unit and downloads the consumption file, process the file, and makes ready for billing as understood by those skilled in the art. The RF radio of each remote collection unit 41, field host unit 51, and/or host computer 61 preferably is a medium to high range radio as understood by those skilled in the art, e.g., preferably in a range of 1 Watt or greater. The RF radio of the field host unit can establish communication 38 to far reaching remote collection units and rake data back, e.g., see FIG. 4, or directly through units establish communication links 36 and also rake data back as desired.

[00112] In the drawings and specification, there have been disclosed a typical preferred embodiment of the invention, and although specific terms are employed, the terms are used in a descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims. The invention has been described in considerable detail with specific reference to these illustrated embodiments. It will be apparent, however, that various modifications and changes can be made within the spirit and scope of the invention as described in the foregoing specification.